










| Wire | Description / Order no. | | | Wire size Dimension | Temp.-area | Form und Setup |
|------|--|-------------------|-------------------|---------------------|--------------------|--|
| | Fe-CuNi | NiCr-Ni | PtRh-Pt | | | |
| 2 | Flexible single conductor PVC sheathed | | | 1,5 – | -20°C up to +80°C |  PVC |
| | 1.00.90.01 | 2.00.09.01 | 3.00.90.01 | 3 mm Ø | | |
| 2 | Flexible wires individually PVC insulated, flat side by side with PVC outer sheath | | | 1,5 – | -20°C up to +80°C |  PVC PVC |
| | 1.00.90.02 | 2.00.90.02 | 3.00.90.02 | 5 x 7 mm | | |
| 2 | Flexible wires individually PVC insulated, twisted, exterior form, exterior PVC insulated | | | 1,5 – | -20°C up to +80°C |  PVC PVC |
| | 1.00.90.03 | 2.00.90.03 | 3.00.90.03 | 8 mm Ø | | |
| 4 | 1.00.90.04 | 2.00.90.04 | 3.00.90.04 | 8 mm Ø | | |
| 2 | Flexible wires individually silicone - insulated, flat side by side silicone insulated | | | 1,5 – | -40°C up to +200°C |  Silicone Silicone |
| | 1.00.90.12 | 2.00.90.12 | 3.00.90.12 | 5 x 7 mm | | |
| 2 | Flexible wire individually silicone - insulated, twisted, exterior form round, outside Silicon isolated | | | 1,5 – | -40°C up to +200°C |  Silicone Silicone |
| | 1.00.90.06 | 2.00.90.06 | 3.00.90.06 | 8 mm Ø | | |
| | 1.00.90.46 | 2.00.90.46 | 3.00.90.46 | | | |
| 2 | Flexible wire Teflon – insulated single twisted and outboard Teflon - insulated | | | 0,5 – | -100°C up to 260°C |  Teflon Teflon |
| | 1.00.90.13 | 2.00.90.13 | 3.00.90.13 | 4 mm Ø | | |
| 4 | 1.00.90.14 | 2.00.90.14 | 3.00.90.14 | 4 mm Ø | | |
| 2 | Flexible wire Teflon – insulated single twisted and glass fibre yarn cable filler outboard Teflon - insulated | | | 0,5 – | -100°C up to 260°C |  Teflon Glass fibre yarn Teflon |
| | 1.00.90.15 | 2.00.90.15 | 3.00.90.15 | 4 mm Ø | | |
| 4 | 1.00.90.16 | 2.00.90.16 | 3.00.90.16 | 4 mm Ø | | |
| 2 | Flexible single wire Teflon - insulated single, twisted, wrapped together Teflon, outside VA braid | | | 0,5 – | -100°C up to 260°C |  VA Teflon Teflon |
| | 1.00.90.17 | 2.00.90.17 | 3.00.90.17 | 4,5 mm Ø | | |
| 4 | 1.00.90.18 | 2.00.90.18 | 3.00.90.18 | 5 mm Ø | | |
| 2 | Flexible wire Teflon - insulated single, twisted, with glass fibre yarn cable filler, Teflon sheath together with external stainless braid | | | 0,5 – | -100°C up to 260°C |  VA Teflon Glass fibre yarn Teflon |
| | 1.00.90.19 | 2.00.90.19 | 3.00.90.19 | 5 mm Ø | | |
| 4 | 1.00.90.20 | 2.00.90.20 | 3.00.90.20 | 5,5 mm Ø | | |

Special cable on demand

Copper cored cable in different versions from 2 up to 8 wire on demand

