

RTD with small connection head

Sensor fix installed

Element	1 x PT 100 / 2 x PT 100, permanently installed Other sensors possible	
Connection-head	Form MA(J) of Aluminium light alloy with M16x1,5 Cable-screw	
Working-temperature	Normal version up to 400 ° C	
Wiring diagram	Datasheet 19.20	
Reaction-time	in Water 0,4 m/s	: $t_{0,5} \approx 5$ s, $t_{0,9} \approx 18$ s
	in Air 1 m/s	: $t_{0,5} \approx 75$ s, $t_{0,9} \approx 3,5$ min

Version With small neck pipe and probe tip extension

Thermowell Material	Fitting	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
1.4571	R1/2"	50	4.92.20.11	4.92.20.12
	R1/4"	50	4.92.20.21	4.92.20.22
Additional price for 50 mm nominal length			4.92.20.10	4.92.20.20

Versions in other dimensions available at short notice

Version Without small neck pipe and probe tip extension

Thermowell Material	Fitting	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
1.4571	R1/2"	50	4.93.20.11	4.93.20.12
	R1/4"	50	4.93.20.21	4.93.20.22
Additional price for 50 mm nominal length			4.93.20.10	4.93.20.20

Versions in other dimensions available at short notice

