

Measuring resistors according to DIN/EN 60751
Glass measuring resistors
 Measuring range -220°C up to +500°C

1 x PT 100 Ohm DIN	D	L	A	Order no.
	Dimensions in mm			1 x PT 100
	2,0	10	20	4.00.00.09
	2,7	13	15	4.00.00.01
	3,0	20	15	4.00.00.02
	2,0	20	15	4.00.00.03
	3,0	25	15	4.00.00.04
	5,0	30	15	4.00.00.05
	4,7	63	15	4.00.00.06
2 x PT 100 Ohm DIN				2 x PT 100
	3,0	38	15	4.00.00.07
	4,7	48	15	4.00.00.08

Ceramic measuring resistors
 Measuring range -220°C up to +600°C

1 x PT 100 Ohm DIN	D	L	A	Order no.
	Dimensions in mm			1 x PT 100
	1,6	20	15	4.00.00.20
	3,0	30	15	4.00.00.21
	5,0	30	15	4.00.00.22
2 x PT 100 Ohm DIN				2 x PT 100
	5,0	30	15	4.00.00.27
	3,0	32	15	4.00.00.28

Thin film measuring resistor
 Measuring range -50°C up to +500°C

1 x PT 100 Ohm DIN	D	L	A	Order no.
	Dimensions in mm			1 x PT 100
Flat shape	2,0	10	15	4.00.00.41
Wire exit straight	2,8	10	15	4.00.00.51
	4,0	5,0	15	4.00.00.61
Angled wire exit	4,0	3,0	15	4.00.00.71
1 x PT 100 Ohm DIN				1 x PT 100
Round shape	2,8	13	10	4.00.00.81
	4,5	13	10	4.00.00.82
2 x PT 100 Ohm DIN				2 x PT100
	4,5	13	10	4.00.00.86

