

### Sheath resistance thermometer with connection head

<b>Element</b>	1 x PT 100 / 2 x PT 100
<b>Connection-head</b>	Form MA(J) of Aluminium light alloy with M16x1,5 Cable-screw Form B of Aluminium light alloy with M20 x 1,5 Cable-screw
<b>Working-temperature</b>	Standard version up to 400°C Special version up to 600°C
<b>Construction</b>	Supply cable in pipe SS (Material No. 1.44541) with internal copper-zircon wire. Mineral isolated welded precision resistor which is also mineral isolated.
<b>Connecting</b>	Datasheet 19.20

Version With small connection head			
Thermowell -Ø	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
3mm	100	4.60.04.11	4.60.04.12
5mm	100	4.60.04.21	4.60.04.22
6mm	100	4.60.04.31	4.60.04.32
Thermowell/ Probe tip	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
3/4 mm x 40mm	100	4.60.04.51	4.60.04.52
5/6 mm x 40mm	100	4.60.04.61	4.60.04.62
6/7 mm x 40mm	100	4.60.04.71	4.60.04.72
Additional price for 100 mm N		4.60.04.10	4.60.04.20

Version With connection head form B			
Thermowell -Ø	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
3mm	100	4.64.04.11	4.64.04.12
5mm	100	4.64.04.21	4.64.04.22
6mm	100	4.64.04.31	4.64.04.32
Thermowell/ Probe tip	N in mm	Order-No. 1 x PT 100	Order-No. 2 x PT100
3/4 mm x 40mm	100	4.64.04.51	4.64.04.52
5/6 mm x 40mm	100	4.64.04.61	4.64.04.62
6/7 mm x 40mm	100	4.64.04.71	4.64.04.72
Additional price for 100 mm N		4.64.04.10	4.64.04.20

